

SafetyWasteCap 2.0

S 60/61 Thread


Universal



THE System
for Solvent Safety

ORIGINAL SAFETY: Innovative & universally usable

- SafetyWasteCap with S 60/61 thread in the new design of generation 2.0.
- More connections thanks to the beveled core - for more applications!
- Maximum flexibility and equipment on a single cap - no adapter required!
- Connections which are not required can be closed with blind plugs.
- Large scope of delivery:
9x Fittings: 3x 1.6 mm, 3x 2.3 mm, 3x 3.2 mm
3x Blind plugs for capillary connection
3x Tube connectors
3x Blind plugs for tube connections



NEW: Ergonomic Design

- Enhanced stability and construction / Improved handling / Easy installation / Smart exchange

NEW: Medical Grade PTFE

- Excellent chemical resistance / Food safe / FDA compliant / Flammability classification V-0 (UL-94)

NEW: PPS Screw Cap

- Autoclavable / sterilisable up to 200 °C / Flammability classification V-0 (UL-94)

Proven: PTFE Body with integrated FKM Seal

- Provides hermetical connection to the container opening and adapts smoothly even to rugged glass surfaces. An additional PTFE layer protects the seal from direct contact to solvents.



☎ **Phone: +49 (0) 61 05 / 30 55 86 - 0**

✉ **e-Mail: info@scat-europe.com**

🌐 **Internet: www.scat-europe.com**

S.C.A.T. Europe GmbH
Waldecker Straße 7
64546 Mörfelden-Walldorf
Germany



Part No.	Description	Thread size	Connections for Ø 1.6 / 2.3 / 3.2 mm OD tubing	Connections for Ø 6.4 - 9 mm ID tubing	Service life (in months)	Unit
307 500	SafetyWasteCap S 60/61, V2.0, Universal	S 60/61	3x	3x	-	1
390 336	Exhaust filter size M, V2.0, with splash protection and change indicator Economy package	GL 14	-	-	2x 6	2