

Oxford Lab Products

BenchMate® L Advanced Manual Pipette

Features and Benefits

Fully Autoclavable and UV Resistant

Ideal for use in sterile applications and cell culture

Durable

The sealing ring is tested to dispense and aspirate 600,000 times; equivalent to 6,250 96-well plates

Solvent Resistant

The pipette body and ceramic plunger have a high tolerance to solvents to prevent corrosion

50/50 Balanced

Composed of lightweight plastic and components in an ergonomic design with a large finger hook and plunger

OXFORD BenchMate L

Enhanced Accuracy and Precision

Hyper blowout system improves dispensing accuracy with a longer second-push stroke

Four Digit Micrometer

Delivers more precise and accurate volume settings compared to a three digit micrometer

Lifetime Warranty*

Durable equipment built to last

oxfordlp.com • info@oxfordlp.com • 1-800-554-4920

^{*}Lifetime warranty only available in the Continental USA

Oxford Lab Products

BenchMate® L Advanced Manual Pipette

Product Overview



Oxford Lab Products

BenchMate® L Advanced Manual Pipette

Ordering Information Specifications

Single Channel Catalog No.	Volume Range (μL)	Increments (μL)	Volume (μL)	Accuracy (systematic error) AC (%)	Precision (random error) CV (%)
OBL-2	0.1 to 2	0.002	0.2 1 2	±12.0 ±5.0 ±3.0	≤6.0 ≤2.5 ≤1.0
OBL-10	1.5 to 10	0.001	1 5 10	±4.0 ±1.0 ±1.0	≤3.0 ≤1.0 ≤0.5
OBL-20	2 to 20	0.02	2 10 20	±5.0 ±1.0 ±1.0	≤3.0 ≤1.0 ≤0.4
OBL-100	10 to 100	0.1	10 50 100	±2.0 ±1.0 ±0.8	≤1.0 ≤0.3 ≤0.3
OBL-200	20 to 200	0.2	20 100 200	±1.0 ±0.8 ±0.8	≤0.5 ≤0.3 ≤0.2
OBL-1000	100 to 1000	1	100 500 100	±1.0 ±0.8 ±0.7	≤0.5 ≤0.3 ≤0.2

Complementary Oxford LP Products

